



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

SPECIFICATION AND DATA SHEET

PRODUCT NAME:

Murco HA 100 Hypo Allergenic Joint Compound

MANUFACTURER:

Murphy Wall Products International, Inc.
201 NE 21st St, Fort Worth, Tx, 76164
800.446.7124

ADVANTAGES:

- Easy mixing
- Less odor
- No toxic emissions
- Easy cleanup

PRODUCT DESCRIPTION:

An easy mixing, powdered all purpose setting compound formulated with no VOC's preservatives, fungicides or petroleum products. It is made with only inert fillers and natural binders. It contains no slow releasing compounds and mixes easily with tap water. It is designed for interior walls and ceilings that are to be painted.

SURFACES PREPARATION:

Surface must be clean and dry. Prime metal and tie wires etc. with rust inhibitive primer. Stained or smoked wall-boards should be primed with stain killing primer. Fill and seal wood surfaces. Concrete ceilings: remove oils, grease, and efflorescence of other deposits. A good quality high solid drywall surface preparation primer is recommended before texturing.

MIXING:

To each bag of HA 100, add approximately 1 gallons of clean water and mix until product reaches a stiff consistency, approximately 5 minutes with a mechanical mixer. Then slowly add approximately 1/4-1/2 gallon of water to reach a proper consistency, for application and mix another 5 minutes.

APPLICATION:

For application use manual hand tools such as taping and putty knives. Can be used with automatic taping tools, however, care should be taken to avoid material setting inside automatic tools. Suitable for use with fiberglass mesh tapes, paper tapes and other patching and joint reinforcements. Apply and feather edges. Should work need sanding it is recommended to wet-sand, or use vacuum sander to limit generating airborne dust. Do not exceed recommended coverage (200 linear foot per bag) as this will lead to poor hide, color differences, and variations in base suction. Two coats may be required on extremely porous surfaces. Let first coat dry thoroughly before applying second coat.



PRODUCT DATA:**Color** Bright White**Setting Time** 20, 30, 45, and 90 minutes (depending on air temperature and humidity)**Storage** Store in a cool, dry place and seal open bags.**Packaging** 25 lb. and 45lb. bag**Coverage** HA 100 covers 200 linear ft per 18 lb bag depending on desired finish.**PRECAUTIONS:**

DO NOT ingest. A NIOSH approved nuisance dust respirator should be used if the air is dusty.

CAUTION: KEEP OUT OF REACH OF CHILDREN**DO NOT TAKE INTERNALLY****DO NOT FREEZE**

MADE IN THE U.S.A