



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

---

## SPECIFICATION AND DATA SHEET

### PRODUCT NAME:

Murco X 47 Unaggregated Texture

### MANUFACTURER:

Murphy Wall Products International, Inc.  
201 NE 21st St, Fort Worth, Tx, 76164  
800.446.7124

### ADVANTAGES:

- Easy Mixing
- Excellent Stand Out
- Lower Cost
- Good Mileage, 20% more cover up
- Works better in both hot and cold weather

### PRODUCT DESCRIPTION:

X 47 is a powdered product used to create various mechanical or hand effects over gypsum wallboard. Paint may be added or applied later. Available in 50 lb bags/ 50 bags per pallet.

### SURFACES PREPARATION:

Surface must be clean and dry. Prime metal, tie wires, etc., with rust inhibitive primer. Stained or smoked wallboards should be primed with stain killing primer. Fill and seal wood surfaces. Concrete ceiling: remove oils, grease, and efflorescence of other deposits. A good quality high-solids drywall primer is recommended before texturing.

### MIXING:

To each bag of X 47 add approximately 3.5 gallons of clean water and mix to a stiff consistency for approximately 5 minutes in a mechanical mixer. Then add approximately 1.5 gallons of water to reach a proper consistency for application. Mix again for 5 minutes more.

### APPLICATION:

Use acoustical spray equipment with either pole guns or Binks 7E 2 guns. Keep pressure as low as needed. High pressure will cause excessive fallout during application. Do not exceed recommended coverage (300-400 per bag) as this will lead to poor hide, color differences, and variations in base suction. Two coats may be required on extremely porous surfaces. Let first coat dry thoroughly before applying second. Maintain 55° F minimum air and surface temperature during application and until surface is dry.



**PRODUCT DATA:**

**Color** Bright White

**Drying Time** Dries to touch in 30 to 60 minutes (depending on air temperature and humidity)

**Storage** Store in a cool, dry place and seal open bags.

**Packaging** 50 lb. bag

**Coverage** X 47 covers 450 - 500 sq ft per 50 lb bag depending on desired finish.

**PRECAUTIONS:**

DO NOT ingest. A NIOSH approved nuisance dust respirator should be used if the air is dusty.

**CAUTION: KEEP OUT OF REACH OF CHILDREN**

**DO NOT TAKE INTERNALLY**

**DO NOT FREEZE**

MADE IN THE U.S.A