



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

SPECIFICATION AND DATA SHEET

PRODUCT NAME:

Hi Coat Interior Drywall Primer

MANUFACTURER:

Murphy Wall Products International, Inc.
201 NE 21st St, Fort Worth, Tx, 76164
800.446.7124

ADVANTAGES:

- A very high quality high build primer can be used in place of skim coating
- Does not require expensive high-pressure spray equipment
- Will not clog spray tips
- Leaves a very slick and durable finish

PRODUCT DESCRIPTION:

A fast drying interior primer and sealer. This product's high solids content often prevents problems commonly referred to as drywall striping, joint banding, and photographing, etc., problems normally associated with varying suction rates by the finish coat of paint. This primer is well suited to working with gloss paints (high-gloss, semi-gloss, satin) and lower cost paints with low solids content or angular sheens.

RECOMMENDED USES:

Hi Coat Primer is formulated specifically to equalize the suction variances between the gypsum panel face paper and the finish joint compound.

SURFACES PREPARATION:

General: All surfaces must be clear of dust, oil, grease, dirt, loose paint and rust. Mildew should be removed with a germicide. Not for use on metal

*The Society for Protective Coatings (SSPC) surface preparation standards should be followed for best performance.

METHOD OF APPLICATION:

Stir thoroughly before and during use. Do not apply when materials, air, or surface temperature is below 50° F in order to protect from freezing.

Thinning is not recommended. However, if required use clean water and do not add more than one gallon of water per 5 gallons of paint.

BRUSH: High quality polyester brush.

ROLL: 3/8-1/2" nap high quality synthetic roller cover.

AIRLESS: Equipment must be clean prior to start. Test your spray pattern and flow before use.

CLEAN UP: Clean tools and equipment with warm, soapy water.



Technical Data

Resin Type	Proprietary latex
Finish	Flat, <5 GU
Colors	White
Viscosity	90 - 95 KU
Solids by Weight	42% \pm 2%
Solids by Volume	30% \pm 2%
Flashpoint	Above 200° F
Density	10.7 - 10.9 lbs./Gallon
Volatile Organic Compounds (VOC)	Less than 5 grams per Liter
Coverage	300 - 350 ft ² /Gallon
Container Size	5 Gallon pails
Dry Time	Dust Free: 1/2 hour Tack Free: 1 hour Recoat: 2 hours; overnight is recommended

CAUTION: KEEP OUR OF REACH OF CHILDREN

DO NOT TAKE INTERNALLY

DO NOT FREEZE

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NOISH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1. 800. 424. LEAD or log on to www.epa.gov/lead

MADE IN THE U.S.A