



Wall Products International, INC.

201 NE 21st St, Fort Worth, Tx 76164

phone: 800.446.7124 or 817.626.1987

fax: 817.626.0821

www.murcowall.com email: murco@murcowall.com

SPECIFICATION AND DATA SHEET

PRODUCT NAME:

Murco Sure Strength

MANUFACTURER:

Murphy Wall Products International, Inc.
201 NE 21st St, Fort Worth, Tx, 76164
800.446.7124

ADVANTAGES:

- Easy mixing
- Less odor
- Less toxic emissions
- Durable hard finish



PRODUCT DESCRIPTION:

Sure Strength is a fast setting and easy sanding all-purpose compound. It may be used for all operations proceeding the final coat in finishing joints, concealing nail heads and corner bead in gypsum wallboard construction. Sure Strength is designed to set up under the worst drying conditions. It also has superior adhesion and virtually no shrinkage. It is particularly useful for finishing joints in manufactured homes where joints commonly crack due to movement during assembly.

SURFACES PREPARATION:

Surface must be clean and dry. Prime metal and tie wires etc. with rust inhibitive primer. Stained or smoked wallboards should be primed with stain killing primer.

MIXING:

To each bag of Sure Strength, add approximately 3/4 gallons of clean water and mix in this stiff consistency for 5 minutes in a mechanical mixer. Then add approximately 1/4-1/2 gallon of water to reach a proper consistency for application.

APPLICATION:

For application use manual hand tools such as taping and putty knives. Can be used with automatic taping tools, however, care should be taken to avoid material setting inside automatic tools. Suitable for use with fiberglass mesh tapes, paper tapes and other patching and joint reinforcements. Apply and feather edges. Should work need sanding it is recommended to wet-sand, or use vacuum sander to limit generating airborne dust. Do not exceed recommended coverage (200 linear foot per bag) as this will lead to poor hide, color differences, and variations in base suction. Two coats may be required on extremely porous surfaces. Let first coat dry thoroughly before applying second coat.

PRODUCT DATA:**Color** Bright White**Setting Time** 20, 30, 45, 80 minutes (depending on air temperature and humidity)**Storage** Store in a cool, dry place and seal open bags.**Packaging** 25 lb. bag**Coverage** Sure Strength covers 200 linear ft per 25 lb bag depending on desired finish.**PRECAUTIONS:**

DO NOT ingest. A NIOSH approved nuisance dust respirator should be used if the air is dusty.

CAUTION: KEEP OUT OF REACH OF CHILDREN**DO NOT TAKE INTERNALLY****DO NOT FREEZE**

MADE IN THE U.S.A